

PLATINUM PRO™ AF-6500 FLOOR FINISH

Urethane enhanced Platinum Pro™ AF-6500 Floor Finish is the ultimate protection against ESD events.

Flooring applied with Platinum Pro™ AF-6500 has ESD protection, safety, gloss, and are easy to maintain.

Using the longest lasting and highest performance available, Platinum Pro™ AF-6800 immediately reduces the cost of maintenance and increases ESD protection.



Benefits

Static Dissipative Protects devices from damage and workers from

explosion/shock

Low VOC Regulatory conformance/personnel safety

High Abrasion Long lasting, reduces repetitive application

High Gloss Aesthetically appealing "wet look"

Low Tribogeneration Eliminates damage to devices

UL Listed Slip resistant

No Formaldehyde/

Phthalates

Safe to use

No Alkalis/Acids Safe to use

Water Based Biodegradable/non-flammable/low odor

Safety Information

Does not contain:

Glycol Ether DE CAS# 111-90-0 Formaldehyde CAS#50-00-0 Dibutyl Phthalate CAS#87074-2

Health1	
Flammability 0	
Reactivity0	
Personal Protection B	

Specifications

Active Ingredients Pro	and the second
receive inigiounicinus i i c	prietary
Surface Resistance (RTT) ANSI/ESD 10 ⁷ S7.1-1994 Vo	-10° Ohms@100 Its
	Minimum (UL ted)
Electrostatic Decay Time EIA 5410.1	Seconds
% Solids 20	% +/- 0.5%
pH 8.0	-9.0
Free Ammonia No	ne
Free Alkali No	ne
Free Acid No	ne
Phosphates No	ne
Color Mi	lky White
Odor Mi	ld
Water Solubility 100	0%
Freeze/ Thaw Stability 3 C	cycles
Shelf Life 1 Y	'ear
Flash Point No	ne
Weight/Gallon 8.6	lbs./gallon
Biodegradable Yes	5
VOC 3.5	%

DIS	TD	IDI	77	ren	D	V
סוע	ını	IDL	JI	EU	D	T.