

# **BR-1800 BURNISHING RESTORER**

## **Description**

Ohm-Shield™ Burnishing Restorer BR-1800 renews static dissipative properties and glossy appearance of Ohm-Shield™ floor finish. Using Burnishing Restorer will extend the static decay properties, surface resistance characteristics and durability of the floor.

The re-coat cycle is extended which reduces the cost of maintaining floors.

Ohm-Shield™ BR-1800 can be used with standard burnishing machines for easy application.



#### **Features**

- Environmentally friendly
- Reduces maintenance cost
- Used at full strength
- Renews the unique protective properties and gloss of Ohm-Shield™ floor finish
- Extends re-coat cycle
- Used with standard burnishing machines
- Coverage: 2,000 sq. ft / gallon

# **Specifications**

Color	Translucent
рН	7-8
Odor	Mild to pleasant
Water Solubility	100%
Hazardous	None
Electrical Resistance per EOS/ESD S4.1	10 <sup>6</sup> -10 <sup>9</sup> ohms
Static Decay Rate	.01 seconds per FTMS 101° C



# **For Serious Protection**

### Ohm-Shield™ AF-5500 Floor Finish

- High abrasion resistance
- Low VOC
- Static dissipative
- High gloss
- Non flaking
- Low cost
- Low tribogeneration
- UL listed
- No formaldehyde or phthalates
- Water based
- Surface resistance (RTT): 10<sup>7</sup>-10<sup>9</sup> ohms @100 volts

DISTRIBUTED BY:				